



ENTERPRISE B-SERIES

# Ultimate M.2 Boot Drive for Servers and Workstations

PASCARI B100

## Sequential Read

Up to 5,000 MB/s

## Sequential Write

Up to 700 MB/s

## Random Read

Up to 450K IOPS

## Random Write

Up to 30K IOPS

## Interface

PCIe 4.0 x4

## Capacity

Up to 960GB

## Form Factor

M.2 2280

## DWPD

1



## Product Features

- NVMe 1.4
- 64 Namespaces
- Power Loss Protection (PLP)
- TCG Opal 2.0 support
- AES-XTS 256-bit Encryption
- Data Integrity and Protection
- End-to-End Data Path Protection
- SECDED
- Sanitize
- NVMe-MI (Management Interface)
- SMBus

**PHISON**

## Solutions - B100P

Form Factor M.2 2280		
Capacity <sup>(1)</sup>	480GB	960GB
Interface	PCIe 4.0 x4	PCIe 4.0 x4
NVMe	1.4	1.4
NAND Flash	3D TLC	3D TLC
Performance <sup>(2,3,4)</sup>		
Sequential Read (MB/s)	4,000	5,000
Sequential Write (MB/s)	300	700
4K Random Read (IOPS)	250K	450K
4K Random Write (IOPS)	15K	30K
Read Latency (Typ., µs)	75	75
Write Latency (Typ., µs)	55	30
Power Consumption <sup>(5)</sup>		
Active (W)	5.6	8.9
Idle (W)	3.5	3.5
Endurance/Reliability		
DWPD <sup>(6)</sup>	1	1
UBER	< 1 sector per 10 <sup>17</sup> bits read	< 1 sector per 10 <sup>17</sup> bits read
MTBF (million hours)	2.0	2.0
Limited Warranty (years)	5	5
Temperature		
Operating Temp. (°C)	0 - 70	0 - 70
Non-Operating Temp. (°C)	-40 - 85	-40 - 85
Physical Dimension		
Length (mm)	80.00	80.00
Width (mm)	22.00	22.00
Height (mm)	4.08	4.08
Weight (g)	12.3	12.4
Part Number		
Non-SED FW	B1802K00480GP01512G00	B1802K00960GP011T0200
SED FW	B1802K00480GP21512G00	B1802K00960GP211T0200

(1) 1 GB = 10<sup>9</sup> bytes.

(2) Sequential Performance is based on FIO on Linux, 128KB data size, with QD=32, 1 job.

(3) Random Performance is based on FIO on Linux, 4KB data size, QD=32, 8 jobs.

(4) Latency is measured with random workloads based on FIO on Linux, 4KB data size, QD=1, 1 job.

(5) Power consumption (average RMS) is measured during the sequential read/write and random read/write operations performed by iometer with the conditions described in (2)(3).

(6) The results of DWPD are obtained in compliance with JESD219A standards.



The data within this specification is subject to change by Phison without notice. Performance numbers may vary based on system configuration and testing conditions. Copyright © 2025 Phison Electronics. All rights reserved.